

CLAIMS

1. Re-sealable bag (1) comprising a closure (13) attached in an interior thereof to one of the front or rear walls (3, 5), with the closure comprising two closure parts (13a, 13b), which are at a distance from a connecting or latching area (19) of the closure (13), which form a connection to the wall (3, 5), and having free edges that are connected undetachably to the wall (3, 5), and with a safety strip (11) above an opening (27) above the latching area (19) of the closure (13), the safety strip (11) is configured so that it can be separated from the wall (3, 5) before an initial opening for exposing the opening (27), both of the closure parts (13a, 13b) are connected to the wall (3, 5) underneath the opening (27) and a cover sheet (15) is attached to an inner one of the closure parts (13a) and also to the wall (3, 5) above and to a side of the opening (27).
2. Bag (1) according to claim 1, wherein edges of the inner and the outer closure parts (13a, 13b) are connected to the front wall (3) by a single common seam (17b) or by two separate bonding, fusing, or sealing seams (17b).
3. Bag (1) according to claim 1, wherein a lower edge of the cover sheet (15) is fixed undetachably at the inner closure part (13a).
4. Bag (1) according to claim 3, wherein the lower edge of the cover sheet (15) is fixed directly on or at a distance to an inner grooved closure (19a).
5. Bag (1) according to claim 1, wherein free edges of the closure parts (13a, 13b) are connected to each other and the closure (13) is produced in one part.
6. Bag (1) according to claim 1, wherein the cover sheet (15) is produced in one part with the closure (13) or with the inner closure part (13a).

7. Bag (1) according to claim 1, wherein the inner closure part (13a) is connected to the wall (3) in a peelable way.